LINE MARKING · ACRYLIC SPORT FLOORS

Overline 367-F

Acrylic latex based high hiding line paint

COLOURS
6 standard colours

1.65 g/cm³	58 %	30 min	min. 2 h	0.300 kg/m²
Density (approx.)	Solids content (wt.)	Touch dry	Overcoating interval	Theor. consumption

Product description

OVERLINE 367-F is a fast drying, 100 % acrylic latex based line marking paint for acrylic sport floors, applicable on concrete or asphalt surfaces. Recommended for bicycle lanes and multipurpose acrylic sport floors.

Product characteristics

- 100 % acrylic latex based topcoat line paint for acrylic sport flooring applications.

Advantages

- Ready to use
- High UV resistance
- Fast drying
- Cost-effective
- High hiding power
- Perfect flexibility
- Easy mixing on site

Position in the system

Finishing — OVERLINE 367-F — THIS PRODUCT
Colour coat — PRECOAT 367-200 range
Cushion layers — UNIRUBBER range
Resurfacer — ACRYLIC RESURFACER 367-30 · LW · 367-43
Primer — ACRYLIC PRIMER 367-28 · AQ PRIMER 2K
Sub-base — Asphalt / concrete

ACRYFLEX-T

Cushioned acrylic tennis court system

ITF classified system surfaces

Technical data (at +20 °C)

Colour	6 standard colours	Overcoating interval	minimum 2 h
Mass density (approx.)	1.65 g/cm³	Theoretical consumption	0.300 kg/m² (1 layer)
Solids content (by weight)	58 %	Application temperature	+14 °C to +35 °C
Touch dry	30 min	Shelf life	12 months

unica | Boytem
BOYTEM BOYA VE KİMYA SANAYİ TİCARET LİMİTED ŞİRKETİ
Factory: Gümüşova OSB 1. Sk. No:4 İç Kapı No:1 Gümüşova / Düzce – TÜRKİYE
T +90 216 304 03 05 · F +90 216 304 12 15
unicaboya.com · info@unicaboya.com

Application procedure

01

Surface preparation

Repair surface defects, cracks and depressions first. Clean the pavement entirely of dust, dirt, mildew, debris and all loose material incl. vegetation. Repairs must be flush and smooth.

02

Mixing

Mix with a slow-speed mixer until homogeneous; add water if needed.

03

Application

Apply in 2 layers with roller or brush: 0.300 kg/m² per coat.

Mixing ratio (by weight)

5 kg

- **5 kg** — OVERLINE 367-F
- **0.5 kg*** — Water*

*The amount of water may vary with ambient temperature. In hot weather up to 5 % more water may be added.

Application conditions

+14 °C – +35 °C

Do not apply the material at temperatures below +14 °C or above +35 °C.

Consumption

0.300 kg/m²

Per coat, applied in 2 layers with roller or brush – depending on surface quality.

Important: coverage rates may vary depending on the surface porosity, ambient temperature and application technique.

Colour range

White | Yellow | Red | Blue | Green | Black

Colour chips are indicative only. Special colours can be produced upon request.

Packaging

- 5 kg steel cans
- 2.5 kg steel cans

Storage

- Store in sealed drums in an indoor, dry warehouse at +15 °C to +35 °C.
- Shelf life: 12 months from the production date in a cool, dry place.
- Do not leave the product outdoors exposed to the sun.

Safety

- Not classified as hazardous.
- Contains no formaldehyde, asbestos, mercury, lead, chromate or their derivatives.
- Contains fire-retardant additives.
- For safe handling and occupational health & safety see the Safety Data Sheet (SDS).

LEGAL NOTE

The statements made on this technical data sheet are believed to be true and accurate and are intended to provide a guide for approved construction practices. UNICA does not make, nor does it authorise any agent or representative to make, any warranty, express or implied, concerning this material, as workmanship, weather, construction, equipment utilised and other variables affecting results are all beyond our control. UNICA warrants only that the material conforms to product specifications, and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall UNICA be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or work performed. UNICA shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.